






Eco-Futural

EcoFutural is a versatile range of high performance commercial windows suitable for use as tilt turn, pivot casement and fixed windows.

- U Value 1.3 W/m²K using double glazed sealed unit
- U Value 1.0 W/m²K using triple glazed sealed unit
- BS 7950 Part 1: 1997 Enhanced Security Performance
- BS 6375 Part 1: 2009 Resistance to Weather







Eco-Futural

EcoFutural is a versatile range of high performance commercial windows suitable for use as tilt turn, pivot casement and fixed windows. Aluminium profiles feature chambered polyamide thermal breaks that provide excellent thermal performance.



Commercial windows suitable for all: Commercial, Retail, Residential, Public, Health Care, Educational applications.

Features

- Polyamide thermal breaks
- Suitable for open in tilt turn, top or side hung casements, pivot and fixed windows
- Weather tested to BS 6375 Part 1:2009
- Security tested to BS 7950 Part 1:1997

Technical Performance

U Value 1.3 W/m²K – using double glazed

sealed unit with centre pane

1.0 W/m²K

1.0 W/m²K – using triple glazed

sealed unit with centre pane

 $0.6~W/m^2K$

 Air
 Class 4, 600pa

 Wind
 Class E900, 900pa

 Water
 Class AE2400, 2400pa

Doc L 2010 Yes

Dimensions

Frame Depth 65mm

Glass O/F 24mm – 51mm

Sash 13mm - 60mm

Test Certification

BS 7950 Part 1: 1997 Enhanced Security Performance

BS 6375 Part 1: 2009 Resistance to Weather



Recommended Design Limits

Tilt Turn

Max Width: 1700mm Max Height: 2400mm Max Weight: 90kg

Pivot

Max Weight Horizontal: 180kg Max Weight Vertical: 120kg

